



Audible Visible Notification

Model: **P2R**

Series: SpectrAlert Advance

Type: Horn Strobe

Description: **The SpectrAlert Advance P2R is a red, two-wire horn strobe with selectable strobe settings of 15, 15/75, 30, 75, 95, 110 and 115 cd.**



Data Sheet (<http://www.systemsensor.com/pdf/AVDS006.pdf>)



Installation Instructions (<http://www.systemsensor.com/pdf/156-2769.pdf>)



Brochure (<http://www.systemsensor.com/pdf/AVBR001.pdf>)



Engineering Specs (<http://www.systemsensor.com/pdf/engineering-specs/horn-strobe.doc>)



CAD Drawing (<http://www.systemsensor.com/cadcentral/dwg/P2R.dwg>)



Specifications: P2R

Color:	Red
Voltage:	Regulated 12DC/FWR or regulated 24DC/FWR
Candela:	Selectable strobe settings of 15, 15/75, 30, 75, 95, 110 and 115 cd
Operating Voltage Range:	8 to 17.5 V (12V nominal) or 16 to 33 V (24 nominal)
DC Max. Operating Current - Strobe:	(see Data Sheet for complete current draw information)
FWR Max. Operating Current - Strobe:	(see Data Sheet for complete current draw information)
Wiring Gauge:	12 to 18 AWG

Operating Temperature: -40°F to 151°F (-40°C to 66°C)

Humidity Range: 10 to 93% non-condensing

Wall mount dimensions (including lens): 5.6"L × 4.7"W × 2.5"D (142 mm L × 119 mm W × 64 mm D)
